

# L-Fab HS

For hi-speed automation of swing gates with leaves up to 4 m or 400 Kg



## Underground installation.

24 Vdc electromechanical gearmotor with magnetic encoder and mechanical stops.

**• Ideal for intensive use and quick manoeuvres: 90° opening in about 6\* seconds.**

## Foundation boxes with mechanical stop on opening:

- in **stainless steel** (LFABBOX4I), ideal for use in extreme conditions;
- **with the cataphoresis paint finish** (LFABBOX4), highly resistant to corrosion.

**Total freedom of choice:** release from inside or outside, lever operated models, freely combinable and easy to operate with just one hand.

**Simple installation:** mechanical stop system on closure. Standard opening max. 110°, optional opening 360°.

**Ideal for intensive use, LFAB4024HS model is compatible with the control unit Moonclever MC824H, with BlueBUS technology, Solemyo and Opera systems:**

- simple programming, by means of a single key;
- automatic memorization of limit switches on opening and closing with self-learning function;
- automatic fault diagnostics;
- programming of pause time;
- pedestrian pass door;
- deceleration on opening and closing;
- obstacle detection with dual technology;
- operation in event of power failure by means of optional rechargeable batteries (PS324);
- provision for connection of latest generation resistive sensitive edges.

\* Considering standard installation, excluding acceleration and deceleration.

Nice **BiDirectional products** indicate the status of the automations and confirm correct reception of the command.

Discover the complete range of BiDirectional products on page 176.

**Yubii** is the new Nice ecosystem that connects all the automations in the home.

Discover all the benefits of the Yubii system on page 170.

## COMMON ACCESSORIES



### CORE

Nice Wi-Fi-Radio Gateway.

Pc./Pack 1



### IT4WIFI

Smart Wi-fi interface to manage gates and garage doors by smart-phone (\*).

Pc./Pack 1



### PS324

24 V battery with integrated battery charger.

Pc./Pack 1



### BMA3

Lever-type key unlock system.

Pc./Pack 1



### MEA5

Lever-type unlock key.

Pc./Pack 4



### BMA1

Accessory for opening up to 360° for gates max. 3.5 m in length.

Pc./Pack 1



### PLA10

Vertical 12 V electric lock (required for gates longer than 3 m).

Pc./Pack 1



### PLA11

Horizontal 12 V electric lock (required for gates longer than 3 m).

Pc./Pack 1



### TS

Signboard.

Pc./Pack 1



### SOLEMYO KIT

The solar power to automate gates, garage doors or barrier gates.

See page 229.

\* Not compatible with the Solemyo kit and PS324


## TECHNICAL SPECIFICATIONS

Code	Description	Pack/Pallet
<b>LFAB4024HS</b>	Non-reversible, 24 Vdc, fast, with magnetic encoder and mechanical limit switch in closing	18
Code	Description	Pack/Pallet
<b>LFABBOX4</b>	Foundation box with cathaphoresis paint finish for LFAB4000, LFAB4024, LFAB4024HS with built-in mechanical stop on opening. Complete with leaf coupling lever	18
<b>LFABBOX4I</b>	Stainless steel foundation box for LFAB4000, LFAB4024, LFAB4024HS with built-in mechanical stop on opening. Complete with leaf coupling lever	18

Code	LFAB4024HS
<b>ELECTRICAL DATA</b>	
Power supply (Vdc)	24
Absorption (A)	7
Power (W)	170
<b>PERFORMANCE DATA</b>	
Speed (rpm)	>> 3 <<
Torque (Nm)	200
Work cycle (cycles/hour)	50**
<b>DIMENSIONAL AND GENERAL DATA</b>	
Protection level (IP)	67
Working temp. (°C Min/Max)	-20 ÷ +55
Dimensions (mm)	375x225x110 h*
Weight (kg)	12,5
Code	LFABBOX4
Weight (kg)	14,4


\* With foundation box. \*\* The indicated value has to be halved if the opening is up to 180° - by using the BMA1 accessory.

### UTILISATION LIMITS



The shape, the height of the gate and the weather conditions can considerably reduce the values shown in the graph to the side.

### DIMENSIONS



## COMPATIBILITY TABLE WITH CONTROL SYSTEMS AND ACCESSORIES

Code	control unit/receiver				transmitter				photocells				flashing light													
	MC200 / Built-in*	MC800 / OXI / OXIBD / OXILR	DPRE00 / OXI / OXIBD / OXILR	DPRE24 / OXI / OXIBD / OXILR	MC424L / Built-in* / OXI / OXIBD / OXILR	MC824H / OXI / OXIBD / OXILR	MC824HR / OXI / OXIBD / OXILR	ERA INTI	ERA ONE	ERA ONE BD	ERA ONE LR	ERA FLOR	NICEWAY	EPS	EPM	EPL	EP5B	EPMB	EPLB	EPMDW	F210	FT210	F210B	FT210B	ELAC	ELDC
<b>LFAB4024HS</b>					•		•	•	•	•	•	•					•	•	•	•					•	•

\* Radio receiver incompatible with Opera system

For swing gates  
Hi-Speed series

For sliding gates

Barrier gate  
operator systems

For garage  
and industrial doors

Control systems  
and accessories

Compatibility table  
and alphabetical index